



EQUIPO SPLIT CASSETTE



CASSETTE INDOOR

Model name			Q8 Cassette Indoor	TSC-018MDS	TSC-024MDS	TSC-036MDS	TSC-048MDS	TSC060MDS
				R410a	R410a	R410a	R410a	R410a
Power supply		V/Ph/Hz		220-240V~/50Hz/1P	220-240V~/50Hz/1P	380-415V~/50Hz/3P	380-415V~/50Hz/3P	380-415V~/50Hz/3P
Cooling	Capacity	Btu/h		18000	24000	36000	48000	60000
	Capacity	W		5300	7200	10500	14000	16119
	Input	W		1732	2432	3723	4636	5694
	Rated current	A		7,87	11,05	7,80	9,30	11,00
	EER	W/W		3,06	2,96	2,82	3,02	2,83
Heating	Capacity	Btu/h		20000	26500	40000	53000	60500
	Capacity	W		5900	7900	12000	16000	17731
	Input	W		1671	2192	3409	5079	5700
	Rated current	A		8,60	11,0	7,20	9,50	11,30
	COP	W/W		3. 53	3,60	3,52	3,15	3,11
Indoor air flow (Hi/Me/Lo)		m ³ /h		1100/950/880	1400/1200/950	1700/1500/1400	1700/1500/1400	1900/1700/1500
Indoor noise level (Hi/Me/Lo)		dB(A)		42/39/35	43/41/37	45/43/41	45/43/41	47/44/43
Indoor dimension	Unit (WxHxD)	mm		830x230x830	830x230x830	830x290x830	830x290x830	830x290x830
	Packing (WxHxD)	mm		950x250x950	950x250x950	950x320x950	950x320x950	950x320x950
Indoor weight	Net	kg		26	27	37	37	37
	Gross	kg		30	31	43	43	43
Panel	Unit (WxHxD)	mm		950x45x950	950x45x950	950x45x950	950x45x950	950x45x950
	Net/Gross	kg		6/9	6/9	6/9	6/9	6/9
Refrigerant	Type			R410A	R410A	R410A	R410A	R410A
Refrigerant pipe	Liquid side	mm		6,35	9,52	9,52	9,52	9,52
	Gas side	mm		12,70	15,88	19,05	19,05	19,05

Outdoor air flow		m ³ /h		2400/1850	4000/2450	4900/2750	6300/4650	6300/4650
Outdoor noise level		dB(A)		49/55	54/58	55/58	57/60	57/60
Outdoor dimension	Unit (WxHxD)	mm		780x605x290	900x650x310	900x805x360	1250x940x340	1250x940x340
	Packing (WxHxD)	mm		883x412x653	1015x720x425	1031x925x447	1365x1030x430	1365x1030x430
Outdoor weight	Net	kg		42	54	79	103	108
	Gross	kg		47	59	87	113	118